

PART NUMBER DESCRIPTION	ITEM 1 HANDLE (QTY)	ITEM 2 LK CYL (QTY)	ITEM 3 O-RING (QTY)	ITEM 4 PUSH BUTTON (QTY)	ITEM 5 SPRING (QTY)	ITEM 6 LK PLATE (QTY)	ITEM 7 SCREW (QTY)	ITEM 8 BOLT (QTY)	ITEM 9 NUT (QTY)	ITEM 10 ZIP-TIE (QTY)	ITEM 11 KEYS (QTY)	ITEM 12 GASKET (QTY)	INSERTION SYMBOL	KEYS SUPPLIED Y/N (QTY)	DIM "A"	DIM "B" MINIMUM TRAVEL	PART MARKING
19466-01 040-0600, PB, 120MM, 3 HOLE, TA183, 2 KEYS		16287-17 (1)											NO	YES (2)			
19466-02 040-0600, PB, 120MM, 3 HOLE, 14803, NO KEYS		29505-02 (1)											YES	NO			
19466-03 040-0600, PB, 120MM, 3 HOLE, D250, NO KEYS		29505-03 (1)											NO	YES (2)	N/A	N/A	
19466-04 040-0600, PB, 120MM, 3 HOLE, TA001-TA010, 2 KEYS		29505-04 (1)						N/A	N/A				NO	YES (2)			
19466-05 040-0600, PB, 120MM, 3 HOLE, C0751, 2 KEYS		16287-18 (1)		80773 (1)	24887-01 (1)	80768-57 (1)							YES				
19466-09 040-0600, PB, 120MM, 3 HOLE, 86, NO KEYS	19592-01 (1)	16287-20 (1)				19465-01 (1)	81789-15 (2)						NO				
19466-10 040-0600, PB, 120MM, 3 HOLE, CAT SP8500, NO KEYS		16287-11 (1)											YES				
19466-12 040-0600, PB, 120MM, 3 HOLE, CAT SP8500, NO KEYS, BLT		16287-03 (1)						20034-01 (1)	20035-01 (1)				NO	40.1±0.5	15.65		
19466-13 040-0600, PB, 120MM, 3 HOLE, ARS1481, NO KEYS								N/A	N/A				NO	N/A	N/A		
19466-14 040-0600, PB, 120MM, 3 HOLE, PADLOCK		N/A	N/A	24033-01 (1)	18127-01 (1)								N/A				
19466-16 040-0600, PB, 120MM, 3 HOLE, PADLOCK W/BLT								20755-01 (1)	20035-01 (1)				NO	16±2	15.65		19466
19466-17 040-0600, PB, 120MM, 3 HOLE, TA001-TA100, 2 KEYS	19592-01 (3)	29505-09 (3)	80773 (3)	24887-01 (3)	80768-57 (3)	19465-01 (3)	81789-15 (6)	N/A	N/A				NO	YES (8)	N/A	N/A	
19466-18 040-0600, PB, 120MM, 3 HOLE, TA183, 2 KEYS, BLT		16287-17 (1)						19918-01 (1)					NO	YES (2)	29.7±3		
19466-19 040-0600, PB, 120MM, 3 HOLE, 14803, NO KEYS, BLT		29505-02 (1)						20034-01 (1)	20035-01 (1)				NO	40.0±2.0	15.65		
19466-20 040-0600, PB, 120MM, 3 HOLE, C0751, 2 KEYS, BLT		16287-18 (1)						19918-01 (1)					YES	YES (2)	29.7±3		
19466-21 040-0600, PB, 120MM, 3 HOLE, NO KEYS	19592-01 (1)	29505-05 (1)						N/A	N/A				N/A				
19466-23 040-0600, PB, 120MM, 3 HOLE, D250, NO KEYS, BLT		29505-03 (1)		80773 (1)	24887-01 (1)	80768-57 (1)	19465-01 (1)	81789-15 (2)	29053-01 (1)	17880-01 (1)			NO	10.2			
19466-25 040-0600, PB, 120MM, 3 HOLE, ARS1481, NO KEYS, BLT		16287-03 (1)						32101-01 (1)	9214-19 (1)				YES	50.0±2.0	15.65		
19466-26 040-0600, PB, 120MM, 3 HOLE, C0751, 2 KEYS		16287-18 (1)						N/A	N/A	17440-01 (1)			NO	N/A	N/A		
19466-27 040-0600, PB, 120MM, 3 HOLE, ARS1481, 2 KEYS, RING		16287-03 (1)						32101-01 (1)	9214-19 (1)	N/A	14472-04-1013 (1)		YES (2)	50.0±2.0	15.65		
19466-29 040-0600, PB, 120MM, 3 HOLE, TA183, 2 KEYS, GASKET, KIT	19592-01 (1)	16287-17 (1)						N/A	N/A	N/A	N/A	19996-01 (1)	NO	N/A	N/A		

- NOTES: UNLESS OTHERWISE SPECIFIED:
- 1 ASSEMBLY SHOWN AND SHIPPED IN UNLOCKED POSITION. SEE TABLE FOR INSERTION SYMBOL.
 - 2 LOCKCYLINDER (ITEM 2) ROTATES 90° IN A CLOCKWISE DIRECTION TO LOCK PUSHBUTTON ASSEMBLY.
 - 3 RECOMMENDED MOUNTING FASTENER TORQUE TO BE 5.6-6.7 Nm.
 - 4 ALL DIMENSIONS EXCEPT WHERE NOTED ARE FOR CUSTOMER AND/OR ISIR PURPOSES.
 - 5 STAMP LOCK PLATE (ITEM 6) WITH PART NUMBER AND DATE CODE PER ES-121. LOCATE APPROXIMATELY AS SHOWN.
 - 6 ASSEMBLE NUT (ITEM 9) FINGER TIGHT FOR VERSION -12, -18, -19 & -20. TORQUE TO 87.6 IN-LBS MIN [9.9Nm] FOR VERSION -16.
 - 7 TORQUE SCREWS (ITEM 7) TO 14.0±3 IN-LBS [1.6±0.3 Nm].
 - 8 19466-17 TO BE KITTED/PACKAGED (3) KEYS ALIKE PER BAG WITH (2) KEYS SEALED IN THE CORNER OF THE BAG.
 - 9 PUSHBUTTON (ITEM 4) TO BE FULLY DEPRESSED WHILE DRIVING BOLT (ITEM 8).
 - 10 -12 ONLY - APPLY LOCTITE 2760 TO BOLT (ITEM 8).
 - 11 -23 ONLY - INSTALL NUT (ITEM 9) ALL THE WAY ONTO SCREW (ITEM 8). INSTALL SCREW (ITEM 8) ALL THE WAY ONTO THE LOCKCYLINDER (ITEM 2). TORQUE 4Nm [30 IN-LB] MIN.
 - 12 -26 ONLY - ATTACH KEYS TO HANDLE (ITEM 1) WITH ZIP-TIE (ITEM 10) TIGHT AGAINST HANDLE (ITEM 1) TO PREVENT KEYS FROM SLIPPING OFF.
 - 13 -27 AND -29 ONLY - SEAL KEY SET (ITEM 11) IN CORNER OF BAG.

TriMark

REV	DATE	BY	PART NUMBER	QUANTITY
D	1.0	2/2	19466	26