

# **Ultra**Abrasive Compound





# **Product Information**

Size	Code	Ctn Qty
0.6kg	G3U601	12
1.1kg	G3U101	6

# **Product Description**

G3 Ultra Abrasive Compound offers unbeatable speed and quality of finish, permanently removing P1500 or finer sanding marks from all modern paint systems.

G3 Ultra is ideally applied using a Farécla G Mop 6" Ultra Yellow Pad (CFY601). The pad was engineered in tandem with the compound to provide a marked performance improvement versus other pads. Our product cap and label stripe are also colour coded to match the transfer on the correct pad for ease of identification.

For best results, follow by polishing with G3 Fine Finishing Compound (G3F101) and G Mop 6" Red Waffle Pad (PFR601). A wipe over with a Farécla Finishing Cloth (FC-3) will remove any remaining residue.

Key Benefits	
Fastest Ever Cutting Action	Unbeatable speed to permanently remove P1500 or finer sanding marks
Permanent Gloss Finish	Provides superb final finish shine in one step for the majority of jobs*.  Scratches are permanently removed leaving a superior gloss finish
Superior Emulsion System	Increased lubrication allows compound to work for longer without drying out
• Clean in Use	Throw off is minimised with surface residue kept lubricated for easy wipe off
Simple and Easy to Use	Forgiving performance makes excellent results achievable for operatives of all experience levels
Silicone Free, Low VOC Content and User Safe	Water-based (non-petroleum) formulation is safe in contact with skin

<sup>\*</sup>One step refers to the repair of lighter coloured paints.



## Use With

#### **Primary Applicator**



G Mop 6" Ultra Yellow Pad (2 pk) CFY601



G Mop 6" Back Plate with White Interface Pad **BPI601** (14mm) **BPI606** (16mm)



Farécla Finishing Cloth (3 cloths) FC-3

#### **Secondary Applicator**



G Mop 6" Ultra Multi-layer Yellow Pad **CFY606** 



**BPI612** (5/8")

G Mop 6" Advanced Back Plate AGM-BP14 (14mm) AGM-BP58 (5/8")



Farécla Finishing Cloth (3 cloths) FC-3


# How To Use




Attach pad to polishing machine

CFY601

**CFY606** (Multi-layer) **G3U101** (1.1kg)



Shake bottle well before use **G3U601** (0.6kg)



Dispense small quantity of product onto surface or pad



Compound at 1500 - 1800rpm



Wipe clean with Finishing Cloth **FC-3** (3 x cloths)

## Technical Information

Appearance: White coloured liquid Viscosity: Medium - high viscosity VOC Content: 24.00% of total product

Relative Density: 1.10

pH: **7.8** 

Paint Type Compliance: HS & UHS

# Fluid Dynamic Technology



The unique process by which 2-phase abrasive particles combine and interact with our superior emulsion system to produce optimal performance.

