H600-R

Product Number: 700H600R

Description

Specifications

Housing Battery compartment Lens On/off switch

Battery type

Light source Colour temperature (Kelvin) Focus Charger operating voltage Charger output Output 30 seconds (lumen) Run time (ca. hours) down to 1 lumen Run time (ca. hours/min.) down to 10% lumens Charging time (hours) Charging level indicator Beam distance (m) Beam width (cm) from 1 m distance Protection class Operating temperature range (Celsius) Charging port Charging port cover Cable for charger, ca. 1 m (supplied in box) Additional data

General Information

Lamp weight (approx.) Lamp dimensions (approx) EAN code box (1 pc) EAN code inner carton EAN code outer carton Harmonized standard code

Packaging

Description Box size (approx.) Box weight (approx.) Carton quantity (pcs) Carton size 6 pcs. (approx.) Carton size 36 pcs. (approx.) Carton weight (approx.) Rechargeable headlamp with 85 + 650 lumens, and red LED

series

POM and aluminium ABS PMMA, optical Top, red rubber 1 x 18650: 3.7V - 2600mAh - 9.62Wh - Lithium rechargeable battery 10W XPL 7500K Twist focus Required: 100V-240V, 50-60Hz Required: DC5V - 1A max (USB connector) 85 (low beam) / 630 (high beam) 22 (low beam) / 12 (high beam) 17.5 (low beam) / 4.2 (high beam) 4.5 4 x LED on battery compartment 70 (low beam) / 200 (high beam) 75 (flood) / 15 (spot) IPX5 / IK07 -20°C ~ +40°C Type C USB Rubber, black USB into charger, Type-C USB into lamp Red LED: 2 lumens - 8 m beam distance

179 g incl. battery Ø3.3 (cylinder) / 4.5 x 6.7 x 5.2 (housing)

"PRO" design colour box x x cm g (inner carton) / (outer carton) x x cm (inner carton) x x cm (outer carton) kg (inner carton) / kg (outer carton)

Features

Rechargeable, lightweight headlamp with red LED Charging indicator (4 x LED), flashing = charging / 4 LEDs trun green = fully charged Switch mode main light: high - low - off Switch off at any stage by holding down switch 2 sec. Switch on again at same stage Interchangeable and rechargeable battery Battery compartment on back of the neck Red LED on back of battery compartment. Separate switch. Switch mode: on - off Cable in cold resistant PVC (down to -40 degrees C) Soft pad and high quality elastic strap (around and over head)



Elwis Lighting A/S Sandtoften 11, 2820 Gentofte, DK www.elwislighting.com - Tel. +45 70 20 10 24