

NOTE

INLET – 3/4"–16 UNF MALE O–RING FITTING
OUTLET – 5/8"–18 UNF MALE O–RING FITTING

INLET AND OUTLET FITTINGS SUPPLIED WITH ALUMINUM THREADED CAPS.
LEAK TEST AT 22 KG/CM^2(300PSI).
FINISHED IN BLACK SEMI–GLOSS POWDER COAT.



	SYM	PCS	PART NO.	DESCRIPTION
	10	2	24–1883	SUPPORT
	9	1	27–0116	OR. FITTING #6
	8	1	27–0115	OR. FITTING #8
	7	1	34–0064	COPPER TUBE 3/8"
	6	1	34–0063	COPPER TUBE 1/2"
	5	1	27–1203	FITTING 3/8"
MCC 37	4	1	27–0390	TRIPOD
MCC 37	3	1	27–0201	M RETURN BEND
MCC 37	2	18	27–0200	RETURN BEND
MCC 37	1	1	21–0325	SLAB COIL (C)

CHECK BY: DATE:

SYM	DESCRIPTION	DATE	BY
1	REVISED PER DCR #0888	JULY 31/97	DP

REVISION

TOLERANCE UNLESS OTHERVISE SPECIFIED

ANG.	0.5/3	3/6	6/30	30/120	120/315	315/1000	1000/2000	OVER 2000
±1°	±0.15	±0.2	±0.5	±0.8	±1.2	±2	±3	±4

THIS PRINT IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTEREST OF MOBILE CLIMATE CONTROL INC.

METRIC

Mobile Climate Control Inc.
Concord – Ontario – Canada

21–0324 CONDENSER

SCALE: NTS BY: CM
DATE: JUNE 27, 1996
DWG: P3–3733 REV: 1