



FEATURES

- High Resolution **7" Digital** TFT LCD
- **Pre-Heating** Control System (below 0°C)
- **Shutter camera support** & **camera heater support**
- Water Resistant (**IP67**)
- **3 Camera Inputs**
- 3 Trigger Inputs
- Automatic Brightness Control
- Auto Scan function
- Auto Power ON/OFF
- NTSC/PAL Auto Switch
- Multi-lingual OSD control
- Tamperproof function
- Built-in Speaker
- Electronic Distance Marker (Parking line)
- Free Input voltage (DC 10V ~ 30V)
- Bracket rails and **Heavy Duty mounting possibility**
- Speedswitch function via tacho signal (in case of frontview purpose)
- Sunvisor – included
- **All connections via one multi-cable (no external controlbox)**

Specifications

Power input	10V~30V DC
Power Consumption	12 Watt Max.
Video System	NTSC, PAL signal Compatible
Panel	7" Digital
Resolution	800 RGB(H) X 480(V)
Format	16:9 wide
Brightness	400cd/m2
Display Mode	Single
Camera Input (3CH)	Mini DIN 4P, 1Vp-p 75Ω
Operating Temperature	-25°C ~ 75°C
Storage Temperature	-30°C ~ 85°C
Dimensions	194(W) X 124(D) X 31.5(H) mm
Weight	Approx. 700g
O.S.D. control	Day & Night Sensor Bright, Contrast, Color, Tint Mirror/Normal image switch, Up/Down image switch Pre-Heating, Trigger activation, Speed switch, Auto-Scan, Auto-Power, Multi-lingual OSD Factory Reset