

Sonic

SIREN AMPLIFIER

POWER AND FUNCTIONALITY FROM THE NO COMPROMISE SIREN



Feature Packed:

- 100W, 11Ω impedance speaker output.
- User configurable tone sets via DIP switches.
- Run input, Horn input, air-horn input.
- Operation from negative inputs or from horn press.
- Reduced volume mode for use in workshops.
- Low volume start up mode, for sensitive areas.
- Data output.
- Available with various country tones
- Relay driver output for horn bypass relay.
- 60W or 100W speaker outputs for day and night Volume levels using one speaker.
- Advanced circuit protection with fault indication:
 - Over/under voltage protection
 - Over temperature protection
 - Surge protection

Benefits:

- 2 year warranty.
- “Mini “ Sized
- Connector kit Included—Harness assembly available separately

Specification:

- 12V or 24V versions available.
- Standby current: > 300mA @ 12VDC
- Maximum operating current: 10A @ 12VDC
- Max. operating temperature: +60°C
- Min. operating temperature: -30°C
- Dimensions: 116 .5 x 106 x 60.0mm
- Weight: 0.85kg
- Approvals: EMC NPIA AES Spec. 5
EMC ECE REG 10.04
- Environmental testing to PHE002

| | |
|--------------|-------------------|
| 9004-12-GB | GB TONE SIREN—12V |
| 9004-24-GB | GB TONE SIREN—24V |
| ME005-000-12 | 12V HARNESS ASSY |
| ME005-000-24 | 24V HARNESS ASSY |

ISO 14001:2004
EMS 73903
ISO 9001:2008
Q05071

9004-SF-1-D
REL 40225