

# S1100-R

# PRO series

Product Name: S1100-R

Product Number: 700S1100-R

Description

Rechargeable torch with 1100 and 120 lumens and sliding focus

## Specifications

Housing	Aluminium
Lens	Ø32mm planoconvex lens
On/off switch	Tailcap Switch
Battery type	18650 (3500mAh)
Light source	CREE XPL LED
Colour temperature (Kelvin)	7500
Focus	Sliding style optical focus system
Charger operating voltage	5V/0.9A
Charger output	Required: DC5V - 1A max (USB connector)
Output 30 seconds (lumen)	120 (low) / 1100 (high)
Run time (hours) down to 1 lumen	22 (low) / 11 (high)
Run time (hours) down to 10% of full lumens	18 (low) / 5.5 (high)
Charging time (hours)	5-6
Charging level indicator	red, green
Beam distance (m)	110 (low) / 300 (high)
Beam width (cm) from 1m distance	110 (flood) / 14 (spot)
Protection class	IPX5 / IK07 / III (torch) - II (charger)
Operating temperature range (Celsius)	between -20°C and 50°C
Charging port	Type-C USB
Charging port cover	Turn-to-cover type-C USB charging port
Cable for charger	1 m (supplied in box). USB into charger, USB C into torch



## General Information

Torch weight (g)	204 incl battery
Torch dimensions (cm)	Ø3.7 x 14.75
EAN code box (1 pc)	5703296700115
EAN code inner carton/display	5703296700122
EAN code outer carton	5703296700139
Harmonized standard code	8513100000

## Packaging

Description	"PRO" design printed box
Box size (cm)	18.6x21.1x8.7
Box weight (g)	625
Carton quantity (pcs)	4 (inner carton) / 16 (outer carton)
Carton size (cm)	25.5 x 19.5 x 19.3 (inner carton) / 40.4 x 41.5 x 26.5 (outer carton)
Carton weight (kg)	2.8 (inner carton) / 11.3 (outer carton)

## Features

- Lightweight torch with sliding focus
- Rechargeable. Hold head and turn tube for access to charging port.
- Charging indicator (1 x LED), red = charging / green = fully charged
- Switch mode: high-off-low-off
- Turn-to-cover Micro USB charging hole
- Supplied with pouch and lanyard
- Supplied with USB C cable for charger



Elwis Lighting A/S, Sandtoften 11, 2820 Gentofte, DK  
www.elwislighting.com - Tel. +45 70 20 10 24

Version 3 04/2021  
© Elwis Lighting 2021  
All details without obligation