

DIGITAL WIRELESS CAMERA SYSTEM (WLAN)



CC3500



EE2178

GENERAL FEATURES

- Power supply voltage: 12V/24V DC
- Wireless standard: IEEE802.11b/g
- Modulation system 11b: DSSS, 11g: OFDM
- Transmission/Reception frequency: 2.4GHz band
- Encryption: 128bit WEP
- Simple pairing method: pairing switch included
- Storage temperature range: -40 ~ +85°C

SPECIFICATIONS

- Camera with transmitter - CC3500
 - Current consumption: less than 250mA
 - Image sensor: 1/3.7 inch CMOS camera
 - Angle of view - Horizontal 115°/ Vertical 85°
 - Operating temperature range: -30°C ~ +70°C
 - Watertightness: IP67
 - Vibration resistance: 6.8G
 - External Dimensions (W x D x H): 80 x 58.23 x 50 mm
 - Weight: 300g
- Receiver - EE2178
 - Current consumption: less than 200mA
 - NTSC Video Out: RCA connector
 - Operating temperature range: -20°C ~ +70°C
 - Watertightness: Non-watertight
 - Vibration resistance: 4.4G
 - External Dimensions (W x D x H): 93 x 108 x 24.5 mm
 - Weight: 236 g