

Suositteltu kaapelipinta-ala 100cm:lle CMP-invertterillä

W	V	Malli	Tuotenro.	Kaapelinpaksuus	Virrankulutus akulta (Ah)
Mukattu siniaalto					
300	12	WHS-300-12V	PC 10421046	3,0 mm ²	29
300	24	WHS-300-24V	PC 10421047	2,0 mm ²	14
600	12	WHS-600-12V	PC 10421048	8,0 mm ²	58
600	24	WHS-600-24V	PC 10421049	5,3 mm ²	29
1000	12	WHS-1000-12V	PC 10421050	13,0 mm ²	96
1000	24	WHS-1000-24V	PC 10421051	8,0 mm ²	48
1500	12	WHS-1500-12V	PC 10421052	33,0 mm ²	163
1500	24	WHS-1500-24V	PC 10421053	21,0 mm ²	81
Puhdas siniaalto					
300	12	INT-300-12V	PC 10421016	5,3 mm ²	29
300	24	INT-300-24V	PC 10421017	5,3 mm ²	14
600	12	INT-600-12V	PC 10421018	13,0 mm ²	58
600	24	INT-600-24V	PC 10421019	13,0 mm ²	29
1000	12	INT-1000-12V	PC 10421020	21,0 mm ²	96
1000	24	INT-1000-24V	PC 10421021	21,0 mm ²	48
1500	12	INT-1500-12V	PC 10421022	21,0 mm ²	144
1500	24	INT-1500-24V	PC 10421023	21,0 mm ²	72