

 **Professional battery tester providing highly accurate results with in-built printer.**

FEATURES

- **Battery 12 V** : test of the voltage and state of charge.
- **Starter 12 and 24 V** : test the start voltage.
- **Alternator 12 and 24 V** : tests no load voltage and charging voltage as well as current undulation during the charge.
- Special feature to test the internal resistance of the battery.
- Printing of the results using integrated thermal printer (no ink required).






INSTANT ANALYSIS

- Battery voltage (6 V to 30 V)
- Available starting power
- Charge state and battery health (%)

BATTERY TYPES

- Compatible with multiple types of lead-acid battery ranging from 30 to 200 Ah :
 - VRLA / GEL / AGM FLAT / AGM SPIRAL sealed batteries
 - STANDARD LIQUID batteries
 - START / STOP batteries (EFB/AGM)

Operating range :

-  EN : 100 > 2000 CCA
-  DIN : 100 > 1400 CCA
-  SAE : 100 > 2000 CCA
-  JIS : Japanese battery
-  IEC : 100 > 1400 CCA (international standard)
- CA/MCA : 100 > 2000 CCA (marine battery)

HIGHLY ACCURATE








- Automatic compensation for external temperature.
- Advanced dynamic resistance measurement technology minimises battery discharge and displays an accurate result which is unaffected by :
 - the surface charge
 - vehicle consumers (lights, various indicators, etc)
 - contact imperfections (worn out terminals/ lugs, unfastened lugs, etc)

PRACTICAL

- Adjustable screen brightness
- Complete test report showing date & time and personalised name.
- Stand-by mode
- Multi-lingual interface
- Removable clamps
- Protection against polarity reversal
- ABS case (acid resistant) and protection against shock.
- Power supply : 1 x 9V battery included



Supplied in a carry bag with 2 paper printer rolls.

		TEST								
		Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE			TEMPERATURE COMPENSATION	mm		kg
12 V	30 >200 Ah	•	• min 6 V	12 V 24 V	1 s	instant	•	55 x 25	120 cm	1.1