

HEPA Filtration System for Ambulances

Compact, noiseless and easy to retrofit



High-efficiency particulate air filters (HEPA) are critical in the prevention of the spread of airborne bacterial and viral organisms. In conjunction with personal protective equipment, this type of filtration greatly reduces the risk of infection for emergency medical service operators.

Webasto filtration systems HFT 300 and HFT 600 are specifically designed to filter the air in the cabin and in the sanitary compartment of ambulances, removing 99.995% particulates corresponding to SARS/COVID-19 virus sizes (0.1 micrometers) and effectively reducing the risk of infection.

Webasto HEPA Filter Top combines two main features to reduce viral loads in ambient air: a very high air volume flow for the rapid and complete filtration of the air every single minute and the extremely high removal efficiency of HEPA H14 filters. The unit complies with the International HEPA Filter standards WHO / CDC / ECDC, requiring 60 air changes per hour for infection control ambulances.

It can be easily installed in any existing emergency vehicle. Moreover Webasto is uniquely able to offer the same level of HEPA-14 filtration used in ambulances also for passenger transport applications.

Product Highlights:

- Removes 99.995% of airborne infections
- HEPA H14 filter - medical grade
- High air exchange rate
- Up to 10 m³ sanitized air every minute
- Two variants available: 300 and 600 m³/h
- Fast and easy installation
- Contamination-free filter replacement
- Automatic filter monitoring device
- Compliant with European Medical Device Directive CE 47/2007
- Meets WHO / CDC / ECDC air filtration guidelines
- CE/UL compliant

Models:
HFT 300 and HFT 600




Special Vehicles

Technical data

	HFT 300	HFT 600
Nominal voltage (V)	12	12
Current consumption @12V (A)	7.1	14.2
Air flow rate (m ³ /h)	300	600
Air filtration level	H14	H14
MPPS Efficiency	99.995%	99.995%
Sound level (db)	<65	<68
Dimensions O.D.x L (mm)	200 x 600	200 x 1200
Weight (kg)	3.1	5.5
Installation position	Any	Any
Temperature Range (C°)	-20° to +60°	-20° to +60°

Example of installation



05/2020 • Errors and omissions expected • Printed in Italy • © Webasto Thermo & Comfort Italy Srl 2020