



FEATURES

- 8" High Brightness TFT LCD with Touch Screen
- Free input voltage (DC10V ~ 30V)
- Auto NTSC-PAL Detection
- 1 A/V input
(RCA, for optional navigation computer or other external device)
- 4 camera inputs (4-pin mini DIN)
- Multiple display modes (FULL, SPLIT, TRIPLE, QUAD)
- Automatic Picture Display (5 independent Triggers)
- Brightness Sensor for automatic DAY/NIGHT setting
- OSD (On Screen Display)
- AUTO SCAN function
- IP67 Waterproof
- High-Sturdy Aluminum Case
- Easy Installation

Specifications

Power input	10V~30V DC
Video System	AUTO NTSC-PAL Detection
Panel	8" Digital
Resolution	800 RGB(H) X 480(V)
Format	16:9 wide
Camera Inputs	4 Inputs (4P Mini Din 1Vp-p)
A/V Input	1 Input, RCA (1Vp-p 75Ω/ Composite, Audio)
Display Mode	FULL, SPLIT, TRIPLE, QUAD
Camera Input (4CH)	Mini DIN 4P, 1Vp-p 75Ω
Operating Temperature	-20°C ~ 65°C
Storage Temperature	-30°C ~ 85°C
Dimensions	218(W) X 150(D) X 50(H) mm
Weight	Approx 2.6kg

Accessories



Sun visor



Camera cable



Power&GPS, A/V cable



Angle Mount Type