

### FEATURES

- 1/3" Color CCD high quality image sensor
- 470.000 pixels (PAL)
- Waterproof Housing (IP69K rating)
- Auto iris
- Normal Image (fixed setting)
- Diagonal 160° Viewing
- Compact Aluminum Housing
- Easy installation (flushmount)
- Temp. - 40°C ~ + 80°C
- Extra thick glass window (3mm)
- Suitable for  $\Phi$  25mm drilling hole
- Various angled washers included
- "CE marked" and "EMC approved"



### Specifications

<b>Image Sensor</b>	1/3" Color CCD with electronic auto iris
<b>Scanning System</b>	PAL 470.000 pixels
<b>Minimum Illumination</b>	0.1 lux
<b>Power range</b>	DC 10V ~ 24V
<b>Power Consumption</b>	DC 12V, 100mA (Max)
<b>Operating Temperature</b>	- 40°C ~ + 80°C
<b>Viewing Angle</b>	123°(H) x 90°(V) x 160°(D)
<b>Material</b>	Compact Aluminum Housing
<b>Dimensions</b>	Head part : $\Phi$ 40.2 mm Main body : $\Phi$ 25.0 mm Total length : 56.44 mm Flushmount depth: approx. 46.50 mm
<b>Wight</b>	Approx. 180g
<b>Accessories</b>	1 set 15° washer, 1 set 6° washer, 1 set straight spacer