

### FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CCD camera (470,000 pixels)
- 1/3" Color CCD high resolution image sensor
- IP69K Waterproof Rating
- Diagonal 130° Viewing
- Normal/Mirror Image switching
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED's
- Built-in Automatic Heater (below +10°C)
- Temp. -40°C ~ 80°C
- Vibration resistant
- Waterproof screw type connector (IP67), 4-pin mini-DIN.
- E-mark.
- ADR approved cable (UV-resistant, resistant to cold temperatures, resistant to most oils, chemicals and weather conditions; meets ISO 4141 and DIN/ISO 6722)



### Specifications

<b>Image Sensor</b>	<b>1/3" Color SONY SUPER HAD II CCD</b>
<b>Scanning System</b>	<b>PAL 470,000 pixels</b>
<b>Resolution</b>	<b>520 TV Lines</b>
<b>S/N ratio</b>	<b>Minimum 44dB (at AGC off)</b>
<b>Minimum Illumination</b>	<b>0 lux (IR LED's on)</b>
<b>Power supply</b>	<b>DC 9 ~ 28V</b>
<b>Power Consumption</b>	<b>DC 12V, 325mA (Heater on) DC 12V, 110mA (Heater off)</b>
<b>Operating Temperature</b>	<b>-40°C to +80°C</b>
<b>Field of View angle</b>	<b>130° (Diagonal), 96.2° (Horizontal), 69° (Vertical)</b>
<b>Dimension</b>	<b>102(W) x 43(H) x 63(D) mm (camera only) 124(W) x 85(H) x 80(D) mm (incl. bracket &amp; sunvisor)</b>
<b>Weight</b>	<b>326g (total weight incl. bracket &amp; sunvisor: 464g)</b>