



FEATURES

- Multiple Quad Control Box
- Free Input Voltage (DC 12V ~ 30V)
- NTSC / PAL Compatibility
- 4 Camera Inputs / 1 AV Input / 1 AV Out
- Multiple Display Mode
(Single, Split, Triple, Quad)
- Automatic Picture Display
(5 Triggering functions)
- Auto Scanning function
- OSD with μ -com
- Easy Setting by Remote Control
- 12V DC OUT
(to activate any monitor with Trigger Input, max.100mA)

Specifications

Power Input	DC 12V ~ 30V (Car Battery)
Power Consumption	Max 24 Watt.
Video System	NTSC / PAL Standard signal
Sync. System	Internal
CA Input (4 CH)	Mini DIN 4p, 1Vp-p, 75Ω
	(Normal, Tilt, Shutter camera compatible)
A/V Output (1 CH)	RCA, Composite Video Signal, 75Ω, 1Vp-p
A/V Input (1 CH)	RCA, Composite Video Signal, 75Ω, 1Vp-p
Operating Temp.	-10$^{\circ}$C ~ 50$^{\circ}$C
Vibration	4G
Dimension	154(W) X 28(H) X 105(D)mm
Supplied acc'y	Power cable (1), RCA Cable (1), Screw Kits (1), Bracket jack (2), Remote Controller (1), RX Module for Remote Controller (1), Instruction manual (1)